



CL17sc Colorimetric Chlorine Analyser with Pressure Regulator Installation Kit, w/o Reagents

Številka izdelka:	8574500
EUR Cena:	Kontakt
Na voljo	

The Next Standard in Chlorine Analysis

The CL17sc online chlorine analyser extends Hach's decades-long legacy as the leader in online chlorine analysis. It uses EPA-approved colorimetric DPD analysis to deliver accurate and reliable measurements of free or total residual chlorine. Whether you use online chlorine measurements to optimise your process or report to regulatory agencies, the CL17sc is the analyser you can trust.

Connection to Hach's SC controller platform gives you more flexibility to transfer, store, and interact with your chlorine measurement data, resulting in better understanding and control of your process, more cost-effective decision-making, and greater peace of mind that your data is always there no matter what happens.

A built-in flow meter, three-colour status light, LED measurement cycle lights, and colorimeter window allow you to quickly and efficiently see that your CL17sc is functioning properly.

The CL17sc can also be used with Hach's Claros Water Intelligence System. With the innovative Claros Mobile Sensor Management, you can view measurements and instrument status anytime, anywhere, on any web-enabled device. Alerts for upcoming maintenance and issues requiring immediate attention are all in the palm of your hand. Detailed, step-by-step illustrated instructions for routine maintenance tasks also allow you to feel confident that you have performed routine maintenance correctly.

- Accurate, reliable online measurement of free or total residual chlorine
- Compliant with US EPA 40 CFR 141.74
- On-screen, guided workflows for routine maintenance tasks
- Comprehensive diagnostic features, including built-in flow meter, multi-colour status light, and colorimeter window
- Available Claros Mobile Sensor Management for measurement data and instrument status anytime, anywhere

Maintenance made easy

The CL17sc reduces your routine maintenance touch time with programmable alerts, simplified tubing replacement, and step-by-step maintenance instructions.

Peace of mind through comprehensive diagnostics

With upgraded features like a flow meter, colorimeter window, multi-colour status light, and predictive diagnostic software, you know your instrument is operating as intended.

Expanded connectivity. Increased flexibility.

By pairing the CL17sc with Hach's SC controller platform, your options increase significantly: internal data logging; external analogue and digital communication alternatives; and multi-parameter instrument flexibility.

The CL17sc is compliant with US EPA regulation 40 CFR 141.74. Both Method 4500-CL G and Method 334.0 can be used for measuring residual chlorine in drinking water.

Specifikacije

Alerts:	Low and high chlorine. Dirty cell. Low and high sample flow.
Certificiranje:	CE compliant with: EN 61326-1, CISPR 11, EN 50581
	ACMA RCM
	South Korea KC Certificate
	North America: FCC Supplier’s Declaration of Conformance, IEC/EN 60529, ICES-003
Čiščenje z zrakom:	Optional with 3/8-inch quick-connect fitting and tubing; 0.003 m ³ /min at 1.38 bar maximum
Delovna temperatura:	5 - 40 °C
Delovna vlažnost:	0 - 90% relative humidity, non-condensing
Dimenzija (v x š x g):	342 mm x 329 mm x 177 mm
Garancija:	24 mesecev
Installation Kit:	Pressure Regulator Installation Kit
Interference :	Other oxidising agents such as bromide, chlorine dioxide, permanganate, and ozone will cause a positive interference. Hardness must not exceed 1,000 mg/L CaCO ₃ .
Kiveta za vzorec:	2.5 minutes
Meja zaznavanja:	0.03 mg/L
Merilno območje:	0 - 10 mg/L Cl ₂
Način montaže:	Wall mount
Napetost (V):	12 VDC, 400 mA maximum (supplied by the controller)
Natančnost:	± 5% or ± 0.04 mg/L (whichever is greater) from 0 - 5 mg/L Cl ₂
	± 10% from 5 - 10 mg/L Cl ₂
Odvod:	½-inch ID flexible hose
Parameter:	Chlorine, free; Chlorine, total residual
Poraba reagenta:	0.5 L of buffer solution and 0.5 L of indicator solution in 31 days
Pretok vzorca:	60 - 200 mL/min through the instrument
Svetlobni vir:	LED, measurement at 510 nm, 1 cm light pathlength
Temperatura vzorca:	5 - 40 °C
Teža:	4.1 kg
Vsebina paketa:	CL17sc Chlorine Analyser with Pressure Regulator Installation Kit, and European User Manual. User provides screws and/or anchors for mounting.
	Hach SC Controller and Reagents are not included, they are sold separately.
Vstop:	¼-inch OD polyethylene tube, quick-disconnect fitting
Vstopni tlak:	0.3 - 5.2 bar supplied to Y-strainer
	0.1 - 0.3 bar supplied to analyser
Zahtevi vzorca:	Y-strainer filtration with 40-mesh screen or higher
Zaščita ohišja:	IP66
Združljivost kontrolnih enot:	SC200, SC1000, SC4500. All controllers sold separately

Vsebina paketa

CL17sc Chlorine Analyser with Pressure Regulator Installation Kit, and European User Manual. User provides screws and/or anchors for mounting. Hach SC Controller and Reagents are not included, they are sold separately.

Obvezni pripomočki

- Kontrolna enota SC4500, Prognosys, 5 izhodov mA, 2 digitalna senzorja, brez vtiča (Item LXV525.99A11551)
- Kontrolna enota SC4500, podpora za Claros, 5 izhodov mA, 2 digitalna senzorja, brez vtiča (Item LXV525.99AA1551)
- Kontrolna enota SC4500, podpora za Claros, 5 izhodov mA, 2 digitalna senzorja, vtič za EU (Item LXV525.99CA1551)