



EZ1032 Phosphate Analyser (Molybdate Blue Method) PO₄-P

Številka izdelka: EZ1032.XXXXXXXX

EUR Cena: Kontakt

Online colorimetric analysis of Phosphate in water (Molybdate Blue Method)

EZ1000 Phosphate Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low µg/L range.

Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator invervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

Flexibility that meets your needs

EZ Series Phosphate Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

Specifikacije

Alarm: 1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts

Analogni izhodi: Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)

Avtomatsko čiščenje: Da

Certificiranje: CE compliant / ETL certified

Demineralised water: For rinsing / dilution

Digital outputs: Optional: Modbus (TCP/IP, RS485)

Dimenzija (v x š x g): 690 mm x 465 mm x 330 mm

Earth connection: Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm²

Garancija: 24 mesecev

Instrument air: Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air

Interference: Arsenic (V), Chromium (VI), Copper (II) > 10 mg/L, Iron (III) > 10 mg/L, Sulphide > 2 mg/L,

Vanadium, Silica > 60 mg/L. Large amounts of colour and turbidity interfere. Fats, oil, proteins,

surfactants and tar.

Kakovost vzorca: Maximum particle size 100 μ m, < 0.1 g/L; Turbidity < 50 NTU

Kiveta za vzorec: 10 min (dilution + 5 min)

Material: Hinged part: Thermoform ABS, door: PMMA

Wall section: Galvanised steel, powder coated

Meja zaznavanja: $\leq 1 \mu g/L$

Merilna metoda: Molybdate blue method (630 nm), conform with APHA 4500-P (C) and (E)

Merilno območje: 0.005 - 1 mg/L PO₄-P

Optional:

0.001 - 0.1 mg/L

0.0025 - 0.25 mg/L

0.0025 - 0.5 mg/L

0.04 - 4 mg/L (with internal dilution)

0.08 - 8 mg/L (with internal dilution)

0.5 - 100 mg/L (with internal dilution)

Moč: 100 - 240 VAC, 50/60 Hz

Max. power consumption: 120 VA

Model: EZ1032

Način premora: 100 - 240 VAC, 50/60 Hz

Odvod: Atmospheric pressure, vented, min. Ø 32 mm

Parameter: Orthophosphate (PO -P)

Precision: 1% full scale range for standard test

Pretok vzorca: 100 - 300 mL/min

Razred zaščite: Protection class: Analyser cabinet: IP44 / Panel PC: IP65

Reagent Requirements: Keep between 10 - 30 °C

Št. vzorca: 1, 2, 4, or 8

Temperatura okolja: $10 - 30 \,^{\circ}\text{C} \pm 4 \,^{\circ}\text{C}$ deviation at 5 - 95% relative humidity (non-condensing)

Temperatura vzorca: 5 - 30 °C

Teža: 25 kg

Umeritev: Automatic, 2-point; frequency freely programmable

Validation: Automatic; frequency freely programmable

Vsebina paketa: EZ1032 Phosphate Analyser, Instruction Manual, 1 x Double Bit Door key, 1 x Mounting

Brackets, 1 x empty 5 Reagent Container with Fittings (for Colour Solution), and 1 x empty 2.5L

Glass Reagent Container with Fittings (for Reductor Solution)

Vzorec: tlak: By external overflow vessel

EZ1032 Phosphate Analyser, Instruction Manual, $1\ x$ Double Bit Door key, $1\ x$ Mounting Brackets, $1\ x$ empty 5 Reagent Container with Fittings (for Colour Solution), and $1\ x$ empty $2.5L$ Glass Reagent Container with Fittings (for Reductor Solution)