

8350 pH combination sensor, ¾", analogue, for fouling samples

Številka izdelka: **08350=C=0005**

EUR Cena: Kontakt
Datum pošiljanja ni prikazan

With CPVC body, 10 m cable and liquid earth rod. T_{max} 80 °C.

Quick response time for accurate temperature compensation (built-in PT100)

Optimised life expectancy: high resistance to poisoning due to the double junction

Chemical resistance of body and junction materials, glass bulb protection against shocks

Maintenance free: Combination gel electrode

Auto-diagnostic of electrodes: glass and reference impedances self-checking

---

Specifikacije

Aplikacija:	Fouling Environments
Delovna temperatura:	Temperature Maximum: 110 °C (230 °F)
Diafragma:	Flat PTFE junction
Dolžina:	150 mm
Dolžina kabla:	10 m
Elektrolit:	KNO_3 and KCl
Garancija:	6 mesecev
Material:	Flat PTFE junction, Guarded glass, Stainless steel ring for impedance measurements, CPVC body
Merilno območje:	0 - 12 pH, ± 0.05 pH
Natančnost:	0,05 pH at 25 °C
Navoj senzorja:	0.75" NPT at both sensor ends
Območje tlaka:	Maximum Pressure: 10 bar (145 psi) at 80 °C
Odzivni čas T95:	10 s
Posebni zapiski:	Liquid earth rod, domed glass with guard
Priključek:	Fixed cable
Referenčna elektroda:	None
Special notes:	Temperature sensor in contact with medium
Temperaturni senzor:	PT100

Tendenca:	< 2 mV/week non-cumulative