



AS950 Refrigerated Sampler, 230 V, with 1 - 20 L Bottle

Številka izdelka:	ASR.CXXX2X11XX
EUR Cena:	Kontakt
Datum pošiljanja ni prikazan	

Sampling has never been this easy.

The AS950 Refrigerated Sampler is an easy and reliable solution for sample collection. With its large and intuitive display, USB data transfer capabilities, and simple one-screen programming, you can save time and streamline the entire sampling process.

Additionally, the AS950 Refrigerated Sampler accurately preserves your samples with an air-sensing thermostat designed to meet international and USEPA guidelines.

Equipped with an error message for easy troubleshooting and corrosion-resistant materials, the AS950 Refrigerated Sampler is the ideal choice for consistent and accurate sampling. Its large, color display, and USB upload and download capabilities make sampling more convenient and efficient.

Even in challenging environments, the AS950 Refrigerated Sampler ensures sample preservation and eliminates uncertainty with an available error warning and status screen.

Investing in the AS950 Refrigerated Sampler means you'll have an easier and more reliable way to collect samples. Start sampling with precision and confidence today by ordering yours.

Easiest and most intuitive operation

The large full colour display and intuitive programming give you access to all your programmable criteria on a single screen - eliminating scrolling through menus and supporting error-free operation.

Most convenient data transfer and programming available

The AS950 is the only sampler that utilises a USB drive to upload and download data and copy programs from one sampler to another.

Confidence in your sampling process

The program status screen instantly communicates alarms, missed samples and program progress for quick and easy troubleshooting.

Resists corrosion

The refrigerated sampler base is designed to endure humid and highly corrosive environments, minimizing damage caused by corrosive gases, rodents, and standing water to guarantee environmental integrity.

Accurate and consistent sample preservations

The custom-designed air-sensing thermostat controls temperature in accordance with USEPA and international guidelines, preserving samples regardless of outside temperatures and conditions.

Specifikacije

Alarm:	Configurable alarms that show on status screen and are recorded in diagnostics alarm logs. Alarms can be set for system diagnostics and logging such as program end, sample complete, missed samples and full bottle. Channel alarms are setpoint alarms for the recorded measurements (channels), such as pH, level and power supply voltage.
Automatic shutdown:	Multiple Bottle Mode: After complete revolution of distributor arm (unless Continuous Mode is selected) Composite Mode: After preset number of samples have been delivered to composite container, from 1 to 999 samples, or upon full container.
Beleženje podatkov:	SAMPLE HISTORY - Stores up to 4000 entries for sample time stamp, bottle number and sample status (success, bottle full, rinse error, user abort, distributor error, pump fault, purge fail, sample timeout, power fail and low main battery). MEASUREMENTS - Stores up to 325,000 entries for selected measurement channels in accordance with the selected logging interval. EVENTS - Ability to store up to 2000 entries in Sample History logging. Records Power On, Power Fail, Firmware Updated, Pump Fault, Distributor Arm Error, Low Memory Battery, Low Main Battery, User On, User Off, Program Started, Program Resumed, Program Halted, Program Completed, Grab Sample, Tube Change Required, Sensor Communication Errors, Cooling Failed, Heating Failed, Thermal Error Corrected.
Bottle Set:	Composite (1) 5.5 gallon polyethylene bottle kit
Certificiranje:	CE, UL
Diagnostika:	View event and alarm logs as well as maintenance diagnostics
Dimenzija:	61 cm x 61 cm x 112 cm
Factory Installed Options:	RAIN/RS485 PORT Accepts Hach Rain Gauge (not included) or can be used as RS485 communications
Frekvenca (Hz):	50 - 60 Hz
Garancija:	24 mesecev
Hladilni sistem:	1/7 HP, 75 Watt, 400 BTU/hr compressor, 120 CFM condenser fan, three-sided wraparound plate type evaporator, rigid foam insulation, air sensing thermostat capable of maintaining sample liquid at 4 °C in ambient temperature to 49 °C maximum; accurate to ±0.8 °C, magnetic door seal
Internal clock:	±1 second per day at 25 °C
Interval vzorca:	Selectable in single increments from 1 to 9999 flow pulses or 1 to 9999 minutes in one minute increments
jeziki:	English, French, Spanish, Italian, German, Portuguese, Chinese
Jeziki uporabniškega vmesnika:	Chinese, English, French, German, Italian, Spanish, Portuguese
Komunikacija:	USB and optional RS485 (Modbus)
Manual sampling:	Initiates a sample collection independent of program in progress
Material ohišja:	22 Gauge Steel (optional Stainless Steel) with Vinyl laminate over-coating (Refrigerator)
Način delovanja:	Continuous or non-continuous
Način premora:	230V
Način vzorčenja:	Pacing: Time weighted, Flow weighted, Time table, Flow table, Event Distribution: Single bottle composite, multi-bottle composite, multi-bottle discrete, bottles per sample, samples per bottle or a combination of bottles per sample and samples per bottle
Napetost (V):	230 V

Natančnost prostornine vzorca:	Typical: $\pm 5\%$ of 200 mL sample volume with: 4.6 m vertical lift, 4.9 m of 3/8" Vinyl intake tube, single bottle, full bottle shut-off at room temperature and 1524 m elevation
Port senzorja:	0
Posoda z vzorcem:	1 x 20 L
Programs:	Dual Programs: Up to 2 sample programs can be run sequentially, in parallel, or according to day of week scheduling; enabling a single sampler to function like multiple samplers
Prostornina vzorca:	Programmable in 10 mL increments from 10 - 10,000 mL
Pump flow rate:	4.8 L/min at 1 m vertical lift with 3/8" intake tube typical
Rain gauge input:	Ne
Refrigeration components and plumbing:	Corrosion protected with conformal all exposed copper tubing is insulated to avoid sweating and condensation
Sample pump:	High-speed peristaltic, dual roller, with 0.95 ID x 1.6 OD cm (3/8" ID x 5/8" OD) pump tube
Sample transport velocity:	0.9 m/s with 4.6 m vertical lift, 4.9 m of 3/8" Vinyl intake tubing, 21 °C and 1524 m elevation
Sample trigger:	When equipped with flow sensor or pH/temperature sensor or peripheral monitoring options, sampling can be triggered upon an upset condition when field selectable limits are exceeded
Sample volume repeatability:	Typical: $\pm 5\%$ of 200 mL sample volume with: 4.6 m vertical lift, 4.9 m of 3/8" Vinyl intake tube, single bottle, full bottle shut-off at room temperature and 1524 m elevation
Sonde vključene:	No
Spomin:	Sample history: 4000 records; Data log: 325,000 records; Event log: 2000 records
Status messages:	Communicates what program is running, if there are any missed samples, when the next sample will be taken, how many samples remain, number of logged channels, time of last measurement, memory available, number of active channels, if alarms were triggered, when alarms were triggered, active sensors and cabinet temperature
Suction Hose Outer Diameter:	1/4" and 3/8" ID PTFE-lined Polyethylene with protective outer cover available in clear and black.
Temperatura:	Operating: 0 - 50 °C Storage: -40 - 60 °C
Teža:	63 kg
Tip osnove:	Vinyl
Tubing:	Pump tubing: 9.5 mm ID x 15.9 mm OD Silicone Intake tubing: 1.0 - 4.75 m minimum length, 1/4" or 3/8" ID Vinyl or 3/8" ID PTFE-lined Polyethylene with protective outer cover (black or clear)
User interface:	Membrane switch keypad with 2 multiple function soft keys
Vertical lift:	8.5 m using 8.8 m maximum of 3/8" Vinyl intake tube at sea level at 20 to 25 °C
Vhodi:	One 0/4-20 mA input for flow pacing
Vhodno izpiranje:	Strainers: Choice of PTFE and 316 stainless steel construction, or all 316 stainless steel in standard size, high velocity, and low profile for shallow depth applications Purge: Air purged automatically before and after each sample; duration automatically compensates for varying intake line lengths Rinse: Intake line automatically rinsed with source liquid prior to each sample, from 1 to 3 rinses

	Retries or Fault: Sample collection cycle automatically repeated from 1 to 3 times if sample not obtained on initial attempt
Vsebina paketa:	1 ea. AS950 controller on vinyl 230 V refrigerated base
	1 ea. Bottle kit (RF010060), includes 1 x 20 L PE bottle w/cap (6494), composite tube support (8886) and full bottle shut-off (8847)
	1 ea. 7 m vinyl intake tubing (920)
	1 ea. strainer (926)
Zaslon: LCD (osvetlitev iz ozadja):	1/4 VGA, Colour; self-prompting/menu-driven program

Vsebina paketa

1 ea. AS950 controller on vinyl 230 V refrigerated base
1 ea. Bottle kit (RF010060), includes 1 x 20 L PE bottle w/cap (6494), composite tube support (8886) and full bottle shut-off (8847)
1 ea. 7 m vinyl intake tubing (920)
1 ea. strainer (926)