



## Hach BioTector B7000i Online TOC Analyser, 0-10,000 mg/L C, 1 stream, 230 VAC

Številka izdelka: B7BAAA044AABAA2

EUR Cena: Kontakt

Datum pošiljanja ni prikazan

### The ideal online TOC Analyser to achieve precise results even for your most challenging applications

Hach BioTector TOC analysers provide maximum uptime and reliability due to an innovative self-cleaning oxidation technology that easily handles difficult samples and significantly reduces maintenance. Unlike traditional TOC analysers, the BioTector eliminates build up issues from salts, particulates, fats, oils and greases that lead to drift and high maintenance. With reliable, continuous monitoring and real-time process control, plant operators can optimise their processes to lower overall plant operating costs. The most advanced system in its class, BioTector products achieve precise results from the simplest to the most demanding applications.

With unique two-stage advanced oxidation technology, the BioTector handles even the most challenging applications involving fats, oils, greases, salts, sludge, and particulates. Oversized tubing eliminates filtration and sample contamination. There's minimal maintenance. No calibration or operator intervention required between service intervals. Provides a quick pay back with cost savings in chemical dosing, waste reduction and optimised processes.

Many additional versions available on request.

#### Worry-free TOC with smart design

The B7000i comes with a built in self-cleaning sample line and reactor. This enables the B7000i to deliver trustworthy results even if your water contains high levels of fats, oils, greases, sludge and particulates or has pH swings.

#### Easy handling

All B7000i come with unique oversized tubing which eliminated the need for filtration and you can be sure to have a fully representative sample. The special tubing also prevents clogging as well as sample contamination.

#### Superior reliability

Using BioTector's internationally proven and innovative Two Stage Advanced Oxidation technology the B7000i delivers maximum reliability, accuracy and availability with a MCert certified uptime of 99.86%. In addition no calibration or maintenance is required between 6-month service intervals.

#### Flexible field of application

Depending on the type of application, the instrument can operate across a very wide measuring range. The B7000i analyser also has multistreaming capabilities with up to 6 process streams possible. Additionally, it can be adapted for indoor or outdoor use.

#### Low cost of ownership

Installing a B7000i provides cost savings through optimising processes by decreasing chemical dosing, waste reduction, reducing samples processes and lowering overall plant operation costs.

---

### Specifikacije

Classification:

197322

Communication: digital:	Modbus RTU, Modbus TCP/IP & Profibus (when the Profibus option is selected, the digital output signals are sent through the Profibus converter with its specific communication protocol)
	Except for Zone 1 certification then Modbus RTU, Modbus TCP/IP & Modbus TCP/IP Redundant is available
Digital outputs:	3 freely programmable system relays
EExp / Nevarno mesto:	Certification options are available to European Standards, (ATEX Zone 1, Zone 2), North American Standards (Class I Division 2) and IECEx Zone 1
Expected Measuring Range:	Standard range < 5000 mg/L
Frekvenca (Hz):	50 Hz
Garancija:	12 mesecev
Izbor območja:	Automatic or Manual Range Selection
Izhod:	1 programmable 4-20 mA analog output signal channel fitted as standard
jeziki:	Slovenian
Kiveta za vzorec:	From 6.5 minutes, depending on range and application
Meja zaznavanja:	0.06 mg/L C
Merilna metoda:	Infrared measurement of CO <sub>2</sub> after oxidation (DIN EN 1484:1997-08, ISO 8245:1999-03, EPA 415.1)
Merilno območje:	0 - 10000 mg/L C
Multi - Sled:	1, 2, 4 and 6 streams
Način premora:	TOC/TIC (230VAC)
Napetost (V):	230 V AC
Odzivni čas :	TOC 6.5 minutes
Oxidation method:	Innovative Two-Stage Advanced Oxidation Process (TSAO) using Hydroxyl Radicals
Parameter:	TOC, TIC, TC, VOC, after correlation COD, BOD, TOG
Particle size:	Up to 2 mm, soft particulates
Permissible Chloride range:	Up to 30 %
Pomnilnik podatkov:	Previous 9999 analysis data on screen in the microcontroller memory and storage of data archive for the lifetime of the analyser in the SD/MMC card.
	Previous 99 fault data on screen in the microcontroller memory and storage of fault data archive for the lifetime of the analyser in the SD/MMC card.
Ponovljivost:	±3 % of reading or ±0.3 mg/L C, whichever is greater, with Automatic Range Selection
Prostornina vzorca:	Up to 8.0 mL
Servisni interval:	6 months service intervals
Št. kanalov:	1
Temperatura okolja:	5 - 40 °C
	Air conditioning and heating options are available.
Temperatura vhodnega vzorca:	2 - 60 °C
Teža:	90 - 120 kg
	Enclosure weight may change depending on system optional features.
Tlak odvoda:	Typically ambient (for applications with high drain pressure, optional systems are available)
User interface:	Microcontroller with membrane keyboard
Vlažnost:	5 - 85 % (non-condensing)
Vsebina paketa:	Includes: B7000i Analyser, Tubing, Fuses, Ferrules, Drain, Acid & Base Dip Tubes, CO <sub>2</sub> Filter & B7000i User Manual
Zaščita ohišja:	IP44; optional IP54 with air purge

Zaslon: LCD (osvetlitev iz ozadja):

High contrast 40 character x 16 line backlit LCD with CFL backlight

---

## **Vsebina paketa**

Includes: B7000i Analyser, Tubing, Fuses, Ferrules, Drain, Acid & Base Dip Tubes, CO<sub>2</sub> Filter & B7000i User Manual