



# **EZ2500 Total Cyanide Analyser**

Številka izdelka: EZ2500.XXXXXXXX

EUR Cena: Kontakt

### Online colorimetric analysis of Total Cyanide in water

EZ2000 Total Cyanide Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low µg/L range.

EZ2000 Total Cyanide Analysers have an internal digestion unit. This additional step prior to analysis allows to measure non-soluble or complexed metal species.

#### Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator invervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

#### Flexibility that meets your needs

EZ Series Total Cyanide Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be extended via an internal dilution option.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

#### **Specifikacije**

Alarm: 1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts

Analogni izhodi: Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)

Certificiranje: CE compliant / UL certified

Demineralised water: For rinsing / dilution

Digital outputs: Optional: Modbus (TCP/IP, RS485)

Dimenzija (v x š x g): 690 mm x 465 mm x 330 mm

Earth connection: Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm<sup>2</sup>

Garancija: 24 mesecev

Instrument air: Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air

Interference: Ions like nitrite > 5 mg/L, sulphide > 100 mg/L and sulphite. Thiocyanate will cause high results.

Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.

Kiveta za vzorec: 75 minutes (dilution + 5 min.)

Material: Hinged part: Thermoform ABS, door: PMMA

Wall section: Galvanised steel, powder coated

Meja zaznavanja:  $\leq 1 \mu g/L$ 

Merilna metoda: Colorimetric measurement at 578 nm using chloramine T method, conform with standard method

APHA 4500-CN €

Merilno območje: 1 - 100 μg/L CN

Optional:

100 - 1000 μg/L (with internal dilution)

Moč: 230 VAC, 50/60 Hz

120 VAC, 50/60 Hz

Max. power consumption: 440 VA

Odvod: Atmospheric pressure, vented, min. Ø 32 mm

Parameter: Cyanide, total

Precision: Better than 5% full scale range for standard test solutions

Pretok vzorca: 100 - 300 mL/min

Razred zaščite: Protection class: Analyser cabinet: IP44 / Panel PC: IP65

Reagent Requirements: Keep between 10 - 30 °C

Št. vzorca: 1, 2, 4 or 8

Temperatura okolja: 10 - 30 °C ±4 °C deviation at 5 - 95% relative humidity (non-condensing)

Temperatura vzorca: 10 - 30 °C Teža: 25 kg

Umeritev: Automatic, 2-point; frequency freely programmable

Validation: Automatic; frequency freely programmable

Vsebina paketa: EZ2500 Cyanide Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets,

4 x empty 2.5L Reagent Containers with Fittings (for Acid, NaOH, Chlor-T & Buffer Solution)

and 1 x empty 2.5L Glass Reagent Container with Fittings (for Colour Solution)

Vzorec: tlak: By external overflow vessel

## Vsebina paketa

EZ2500 Cyanide Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 4 x empty 2.5L Reagent Containers with Fittings (for Acid, NaOH, Chlor-T & Buffer Solution) and 1 x empty 2.5L Glass Reagent Container with Fittings (for Colour Solution)